



The consistent further development of the Combi PET model permits additional time saving

> by the automatic seal feeding (direct from the magazine)

The 13 mm and 16 mm PET strapping tool cuts tension-free and thus splice-free.

High degree of safety through high tension and reliable seal.

# The manual strapping tool for PET strap with seal magazine



- Patented seals in magazine for trouble-free operation
  - Time saving, flexible, and easy to operate
  - Reliable crimp with seal
- High sealing strength up to 75% of strap strength
- For 13 mm (1/2") and 16 mm (5/8")

  PET strap widths



# central strapping systems

#### "Pneumon ST"



pneum. tool, sealless

" Combi PP/PET"



manual tool, with seal



manual tool, sealless



manual tool, with seal



manual tool, with seal



"RS 80 ST, with sealer"



manual tool, with sea

#### Strap dispenders



### **Model list CoMag PET**

Stock No.	Model	Strap width	Strap type	Thickness of
				plastic strap
079055	MKUC PET	13 mm	PET	0.5 – 0.8 mm
079056	MKUD PET	16 mm	PET	0.5 – 0.8 mm

## **Seals for CoMag PET**

Model	Strap width	Seal/Type	Stock No.	Unit
MKUC PET	13 mm	MHUC PET 13 x 33 x 0.8 mm	029805	2500 pieces
MKUD PET	16 mm	MHUC PET 16 x 33 x 0.8 mm	029808	2500 pieces

#### **Specifications**

Model	Length/width/heigth	Net weight	Gross weight	Seal
				Crimp
MKUC PET	580 x 105 x 165 mm	3.6 kg	4.2 kg	lock
				with
MKUD PET	580 x 105 x 170 mm	3.6 kg	4.2 kg	seal

### Accessories

Stock No.	Nomenclature
079392	Hole punching pliers for customs purposes, for plastic strap
079395	Plastic strap cutter "Seal-EX"
079351	Uncoiler carriage "Luxus" for plastic strap, with brake, 400 mm core diameter
079352	Uncoiler for screw-on mounting for plastic strap, with brake, 400 mm core diameter
079355	Uncoiler carriage "Standard" for plastic strap, with brake, 400 mm core diameter
079356	Uncoiler carriage "Spezial" for plastic strap, with brake, 200/280 mm core diameter